

# 2 Door Kit - PoE+

The 2 Door Kit - PoE+ features the Controller 6000 2 Door variant, which can be configured with a maximum of two doors associated to the Controller. This delivers a cost effective solution for distributed one to two door access control using an Ethernet connection for both power and data supply.

## PoE+

PoE+ is a standard for passing electrical power along with data on Ethernet cabling. Many organizations are implementing IT infrastructures that allow them to power field devices, such as Voice over IP phones and IP cameras, via PoE+ enabled switches and routers. PoE+ enabled switches and routers are typically backed up via an Uninterruptable Power Supply (UPS), providing an alternative to more traditional battery backup methods.

## C6000 2 Door Kit - PoE+

The Controller 6000 2 Door PoE+ Kits remove the need for a dedicated mains-fed power supply and battery backup for each Controller. The kit contains a PoE+ splitter, which delivers power for up to 2 typical access controlled door locks with related card readers, along with the Controller 6000 2 Door Kit hardware.

### Benefits include:

- Cost effective means for providing distributed access intelligence at every door
- Minimized costs when connecting a door beyond the range of a RS485 run, or where only an Ethernet connection is available, (e.g. a guard gate house that already has an Ethernet connection, where the cost of running a new RS485 cable would be prohibitive)
- Multiple sites with only one to two doors can connect to once centralized security system - Command Centre.
- Leverage an organization's existing IT infrastructure, (e.g. powering Controller and door hardware via an organization's Power over Ethernet (PoE+ capable switch or router) to manage security hardware



## What's in the kit?

### The 2 Door Kit - PoE+ includes:

- 1 x Single Cabinet
- 1 x 2 Door Controller 6000
- 1 x Controller 6000 I/O Mounting Plate
- 1 x HBUS 8 In 2 Out Door Module, or  
1 x HBUS 4 In 2 Out Door Module - Wiegand
- 1 x PoE+ Splitter

## Technical Specifications

Product numbers		Command Centre compatibility
<b>C302900</b>	Controller 6000 2 Door Kit - PoE+ (HBUS variant)	7.30 or later
<b>C302901</b>	Controller 6000 2 Door Kit - PoE+ (Wiegand variant)	7.30 or later
<b>C302902</b>	Controller 6000 2 Door Kit - PoE+ (Wiegand via HBUS)	7.90 or later

Components		C302900	C302901	C302902
<b>C300111</b>	1 x 2 Door Controller 6000	✓	✓	✓
<b>C200003</b>	1 x Controller 6000 I/O Mounting Plate	✓	✓	✓
-	1 x PoE+ Splitter	✓	✓	✓
<b>C200100</b>	1 x Single Cabinet	✓	✓	✓
<b>C300660</b>	1 x HBUS 8 In 2 Out Door Module	✓		
<b>C300665</b>	1 x HBUS 4 In 2 Out Door Module - Wiegand			✓

Dimensions	
<b>Height x Width x Depth</b>	285 x 285 x 100 mm (11 <sup>1/4</sup> x 11 <sup>1/4</sup> x 4 in)
<b>Weight</b>	3 kg (6.61 lb)

©2013 Gallagher Group Ltd. Gallagher is an ISO 9001:2008 certified supplier. All rights reserved. The products described in this document are subject to continuous development and improvement so specifications and information may change without notice. System configuration, network capacities and the volume of system activity affect performance.

### Gallagher World Headquarters

181 Kahikatea Drive, Melville, Hamilton 3204  
New Zealand

**Phone** +64 7 838 9800

**Email** [security@gallagher.com](mailto:security@gallagher.com)



### Regional Offices

Americas	+1 877 560 6308
Asia	+852 2946 9641
Australia	+61 3 9308 7722
India	+91 98 458 92920
Middle East	+971 4 566 5834
South Africa	+27 11 974 4740
United Kingdom / Europe	+44 2476 64 1234

### Disclaimer

Please note that information contained in this document is intended for general information only. While every effort has been taken to ensure accuracy as at the date of the document, there may be errors or inaccuracies and specific details may be subject to change without notice. Copyright © Gallagher Group Limited.