

Exit Devices

Gallagher provides robust and intuitive Touch to Exit and Emergency Exit egress devices. These devices can be integrated with Gallagher Command Centre or another control system to provide a complete and controlled exit solution.



Touch to Exit Device

Features and benefits

- Light touch activation
- Fits standard electrical flush box
- Vandal-resistant and easy to clean
- Output for real-time status monitoring
- Self-calibrating switch
- No moving parts
- Sounder to provide audible confirmation of operation
- Two LED indicators provide visual confirmation for heartbeat (Red) and operated (Green).



Emergency Exit Device

Features and benefits

- Field resettable unit, a reset tool is supplied with every unit
- Fits standard electrical flush box
- No breaking of glass to operate
- Two outputs; one set to break lock power and one set for real-time status monitoring
- Ancillary input for remote operation of sounder
- Minimal moving parts.



Unmonitored Emergency Exit Cover Monitored Emergency Exit Cover

This cover is available in both a monitored and unmonitored configuration, the key features are:

- Designed to suit the Emergency Exit Device for the purpose of deterring unintended or malicious activation in public areas
- Two potential outputs; one for local audible indication, and one for status monitoring (C861203 only)
- The cover is secured behind the Emergency Exit Device to prevent removal
- The cover is designed to latch closed so as to make the operation of it a deliberate action
- Durable polycarbonate cover is easily cleaned, and weather resistant for external use
- Minimal moving parts
- Text and graphics will not deteriorate over time

Gallagher Exit Devices

Part numbers	
C861200	Touch to Exit
C861201	Emergency Exit
C861202	Unmonitored Emergency Exit Cover
C861203	Monitored Emergency Exit Cover

Technical Specifications

	Power requirements	Outputs	Compliance
Touch to Exit	<ul style="list-style-type: none"> ▪ 9 to 16VDC ▪ 50mA at 13.6 VDC 	<ul style="list-style-type: none"> ▪ 2 x Clean NO and NC outputs (opens on activation) ▪ Contacts are rated at 1 AMP DC 	<ul style="list-style-type: none"> ▪ RCM
Emergency Exit	<ul style="list-style-type: none"> ▪ 9 to 16VDC (if using on board sounder) ▪ 10mA at 13.6 VDC 	<ul style="list-style-type: none"> ▪ 2 x Clean NO and NC outputs (opens on activation) ▪ Contacts are rated at 1 AMP DC 	<ul style="list-style-type: none"> ▪ RCM ▪ Complies with BS 5839 Pt 2. Standard for "Break-Glass Panels"
Monitored Emergency Exit Cover	Switching voltage max is 30Vdc, 200mA	<ul style="list-style-type: none"> ▪ Output to activate the Emergency Exit Device audio ▪ N/C output for status monitoring (opens on activation) 	

Dimensions

Touch to Exit/Emergency Exit Device			
Dimensions	Height x Width x Depth	117 x 75 x 14mm (4.6 x 3 x 0.5in)	
	Weight	200g (7oz)	
Monitored/Unmonitored Emergency Exit Cover			
Dimensions	Height x Width x Depth	137 x 87 x 18mm (5.4 x 3.4 x 0.7in)	
	Weight	150g (5.2oz)	

GALLAGHER WORLD HEADQUARTERS

Kahikatea Drive, Hamilton 3206
Private Bag 3026, Hamilton 3240
New Zealand

TEL: +64 7 838 9800
EMAIL: security@gallagher.com



REGIONAL OFFICES

New Zealand..... +64 7 838 9800
Americas..... +1 877 560 6308
Asia +852 3468 5175
Australia +61 3 9308 7722
India +91 98 458 92920
Middle East..... +971 4 5665834
South Africa +27 11 974 4740
United Kingdom / Europe..... +44 2476 64 1234

DISCLAIMER: This document gives certain information about products and/or services provided by Gallagher Group Limited or its related companies (referred to as "Gallagher Group"). The information is indicative only and is subject to change without notice meaning it may be out of date at any given time. Although every commercially reasonable effort has been taken to ensure the quality and accuracy of the information, Gallagher Group makes no representation as to its accuracy or completeness and it should not be relied on as such. To the extent permitted by law, all express or implied, or other representations or warranties in relation to the information are expressly excluded. Neither Gallagher Group nor any of its directors, employees or other representatives shall be responsible for any loss that you may incur, either directly or indirectly, arising from any use or decisions based on the information provided. Except where stated otherwise, the information is subject to copyright owned by Gallagher Group and you may not sell it without permission. Gallagher Group is the owner of all trademarks reproduced in this information. All trademarks which are not the property of Gallagher Group, are acknowledged. Copyright © Gallagher Group Ltd. All rights reserved.

3E9822 - 07/19