Security Insulators

Specialized high performance security insulators designed for Gallagher's monitored pulse fence.

Gallagher security insulators are crafted from UV stabilized material for long life and strength, these insulators are suitable for a wide range of wire types. Designed to fit securely to galvanised steel security posts, these insulators offer superior protection against arcing.

Wire at any angle

Regardless of topography and elevation changes, the omni directional design of the Gallagher Pull Through Elevation Strain can accommodate the angle required.

Maximum wire tension:

- 60kg (long term load)
- 200kg (peak load)

Tracking distance:

48mm

Material:

UV stabilized glass filled nylor

Material:

+/- 45° in all directions

Advanced arc protection

Dual shield design gives the Enhanced Intermediate Insulator superior contamination resistance. The increased tracking distance allows the insulator to operate effectively with higher voltages and in challenging environmental conditions.

Available in two configurations; hard claws for robust fixtures, and break away for reactive alarms from even minimal attempts to scale the perimeter.

Breakaway load (G27606):

20kg

Tracking distance:

81mm

Material:

UV stabilized HDPE

Maximum operational angle:

1-2° vertical down

3-5° vertical up

2-3° horizontal forward

16-32° horizontal back

Pull Through Elevation Strain



Enhanced Intermediate Insulator





The special design of the breakaway claw makes a fence difficult to traverse without setting off alarms. The weight of the intruder causes the support claw to snap, and the resulting contact to surrounding security wires causes an immediate alarm state.

A combination of breakaway and hard claws can provide an even more effective solution, depending on the requirements of the perimeter.



Technical Specifications

Part nui	nbers
G27606	Enhanced Intermediate Insulator - Breakaway (x100)
G27608	Enhanced Intermediate Insulator - Breakaway (x500)
G27706	Enhanced Intermediate Insulator - Hard claw (x100)
G27708	Enhanced Intermediate Insulator - Hard claw (x500)
G22905	Pull Through Elevation Strain

Features	G27606	G27706	G22905
Breakaway	✓	-	-
Ext corner	-	-	✓
UV stable	✓	✓	✓
HV+ compatible	✓	✓	✓
Material	HDPE	HDPE	GF Nylon
Tracking distance	81mm	81mm	48mm
Colour	Black	Black	Black
Pack size	100/500	100/500	50

Dimensions

Security insulators	G27606	G27706	G22905
Dimensions - H x W x D	47mm x 45mm x 60mm	47mm x 45mm x 60mm	43mm x 46mm x 80mm

GALLAGHER WORLD HEADQUARTERS

Kahikatea Drive, Hamilton 3206 Private Bag 3026, Hamilton 3240

TEL: +64 7 838 9800 EMAIL: security@gallagher.com







REGIONAL OFFICES

New Zealand	+64 7 838 9800
Americas	+1 877 560 6308
Asia	+852 3468 5175
Australia	+61 3 9308 7722
India	+91 98 458 92920
Middle East	+971 4 5665834
South Africa	+27 11 974 4740
United Kinadom / Furone	+44 2476 64 1234

products and/or services provided by Gallagher Group Limited or its related companies (referred to as "Gallagher Group Limited or its related companies (referred to as "Gallagher Group). The information is indicative only and is subject to change without notice meaning it may be out of date at any given time. Although every commercially reasonable effort has been taken to ensure the quality and accuracy of the information, Gallagher Group makes no representation as to its accuracy or completeness and it should not be relied on as such. To the extent permitted by Jaw, all express or implied, or other representations or warranties in relation to the information are expressly excluded. Neither Gallagher Group nor any of its directors, employees or other representatives shall be responsible for any loss that you may incur, either directly or indirectly, arising from any use or decisions based on the information is subject to copyright owned by Gallagher Group and you may not sell it without permission. Gallagher Group is the owner of all trademarks reproduced in this information. All trademarks which are not the property of Gallagher Group, are acknowledged. Copyright © Gallagher Group Ltd. All rights reserved.



