Controller 6000 PoE + Kit

Gallagher provides a Power over Ethernet Plus (PoE+) Controller solution, to cater for site architectures leveraging distributed ethernet networks.

Features and benefits:

The kit comes pre-wired allowing quick and easy installation; It provides control of up to two doors including electric locks^{*} within the parameters of the PoE+ standard, which is specified at 25.4 watts over a CAT5e network segment of up to 328ft (100m).

The Gallagher PoE+ Kit includes:

- Gallagher Controller 6000 (and single cabinet);
- Gallagher GBUS Universal Reader Interface (either Cardax IV or Wiegand) and;
- PoE + Splitter

PoE+ Kit Options

- C205900 Gallagher Controller 6000 PoE + Kit - Cardax IV readers.
- C205901 Gallagher Controller 6000 PoE + Kit - Wiegand readers.

*Requires PoE IT network infrastructure





Technical Specifications

C205900 Gallagher Controller	6000 PoE + Kit - Cardax IV readers			
C205901 Gallagher Controller	6000 PoE + Kit - Wiegand readers			
Gallagher Controller 6000 PoE+ Kit		Gallagher Reader	Wiegand Reader	
Product detail	Doors supported in PoE+ mode	2	2	
	Readers provided	2	2	
	4-state balanced inputs	8	4	
	Relay Outputs (Form A dry contact C/O contacts)	2	2	
	PoE+ system power maximum	25.5 watts, which equates to a load of approximately 2 Amps at 13.6Vdc.		
	Controller 6000 functionality	Refer to the Gallagher Controller 6000 datasheet for specifications		
	Power Source Equipment device specification#	PoE+ (IEE802.3at), 25.5 watts		
Power	Relay Specification	Resistive load	3 Amps at 24vDC/AC	
		Inductive load	1 Amps at 24vDC/AC	
	Current	Equipment & locks is 1500 mA. The capacity of the Controller 6000 PoE+ Kit is as follows:		
		PoE+ Controller with one T10/11/12 Reader	500mA (1000mA free)	
		PoE+ Controller with two T10/11/12 Readers	550mA (950mA free)	
		Electric locks	Approx 1000mA (approx 500mA free)	
Minimum requirements	Software			
Communications	Transfer speed			
	Max distance Controller to PoE switch	100m (328ft)		
	Max distance to Gallagher Reader	183m (600ft)		
	Max distance to Gallagher Wiegand	137m (450ft)		
	Network connectivity	10/100BaseT, RJ45		
	Cable specification	Reader data - 4 core security cable or Cat5		
Shipping dimensions	Height x width x depth	292 x 292 x 102mm (11.5 x 11.5 x 4in)		
Additional notes	 Allowance has been made for in-rush cu # Equipment not provided Cable lengths stated are for data only. D Approximate length. Please refer to the 	C power cable must be of a gauge that provides a	minimum of 12 volts DC at the reader termi	

GALLAGHER WORLD HEADQUARTERS

Kahikatea Drive, Hamilton 3206 Private Bag 3026, Hamilton 3240 New Zealand

TEL: +64 7 838 9800 EMAIL: security@gallagher.com





Telarc. Registered

REGIONAL OFFICES

New Zealand	+64	7 838	9800
Americas	+1 87	7 560	6308
Asia	+852	3468	5175
Australia	+613	9308	7722
India+	91 98	4589	2920
Middle East	+971	4 566	5834
South Africa	+27 1	1974	4740
United Kingdom / Europe+	44 24	76 64	1234

DISCLAIMER: This document gives certain information about products and/or services provided by Gallagher Group Limited or its related companies (referred to as "Gallagher Group"). The information is indicative only and is subject to change without notice meaning it may be out of date at any given time. Although every commercially reasonable effort has been taken to ensure the quality and accuracy or completeness and it should not be relied on as such. To the extent permitted by law, all express or implied, or other representations or warranties in relation to the information are expressly excluded. Neither Gallagher Group nor any of its directors, employees or other representatives shall be responsible for any loss that you may incur, either directly or indirectly, arising from any use or decisions based on the information subject to copyright owned by Gallagher Group and you may not sell it without permission. Gallagher Group and you may not sell further the property of Gallagher Group, are acknowledged. Copyright © Gallagher Group. Ltd. All rights reserved.



security.gallagher.com